

TECHNICAL DATA SHEET NO: SCRIMTAPE

VERSION: 3/ 20th January, 2014 DATE OF ISSUE: 9/11/2014 PAGE: 1 OF 2

# **EVERBUILD EUROSCRIM TAPE**



Colour	<b>Product Code</b>	Pack Size	<b>Box Qty</b>
White	2EURO100	100mm x 90Mtr	12
White	2EURO48	48mm X 90Mtr	24

## **Product Description**

EVERBUILD EUROSCRIM TAPE is a fibreglass re-enforced plasterers tape on a roll which is backed with a pressure sensitive adhesive.

#### **Benefits**

- Quick and easy to apply.
- Self-adhesive eliminates the need for pre-plastering.
- Flexible won't bubble or blister.

## **Areas For Use**

- For jointing dry walling.
- For repairing/jointing over large cracks in plaster.
- Repairing/jointing in ceiling work.

#### **Limitations**

- Ensure surfaces are completely clean before applying tape.
- Never overlap the tape, always butt the joint.
- When applying jointing compound or plaster, ensure complete penetration through the tape to achieve optimum adhesion.

## **Surface Preparation**

All surfaces must be clean, dry, sound and free from oil, grease and dust.

## **Application**

Place tape into position and apply directly to joint or crack pressing down firmly to ensure good adhesion. For crack and hole repairs, the tape must be extended at least 25mm from the edge of the area to be repaired, butting (never overlapping) the tape.

Once the tape is in position, cover with jointing compound or plaster, ensuring the plaster or jointing compound penetrates the tape to achieve optimum adhesion.



TECHNICAL DATA SHEET NO: SCRIMTAPE

VERSION: 3/20th January, 2014 DATE OF ISSUE: 9/11/2014 PAGE: 2 OF 2

**Specific Data** 

Pressure sensitive **Adhesive Type** 

## **Health & Safety**

Consult MSDS for full list of hazards.

## **Storage**

Store in original container in cool dry conditions. Keep away from sources of ignition.

## **Shelf Life**

Storage life 12 months in tightly sealed, undamaged containers.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.