

EVERBUILD SUPERLIGHT 2 PART HIGH PERFORMANCE WOOD FILLER

Colour	Product Code	Pack Size	Box Qty
Light Stainable	2PSUPLT3	370GRM	6
Light Stainable	2PSUPLT9	900GRM	6

Product Description

EVERBUILD SUPERLIGHT 2 PART HIGH PERFORMANCE WOOD FILLER has been specially developed using lightweight particle medium to provide a high performance wood filler that is exceptionally easy to sand down and will accept all common types of wood stain. EVERBUILD SUPERLIGHT offers a superior level of stainability than heavier particle fillers. The lightweight nature of the material also provides excellent slump resistance in vertical joints and allows deep gaps to be filled in one application. Once mixed the filler sets hard to provide a tough, long lasting repair to all woods and can be filled to any depth.

Benefits

- 2-Part lightweight system – durable, long lasting and shatterproof.
- Excellent staining characteristics, can be stained, painted, varnished or dyed.
- Suitable for deep vertical applications.
- Chemical cure product – sets in 30 minutes to any depth.
- Sandable in 30 minutes.
- Can be drilled, nailed, planed and carved when dry.
- Flexes with the natural movement of the wood.

Areas For Use

- Repairing wood damaged by wet rot (in conjunction with EVERBUILD WET ROT WOOD HARDENER) in both interior and exterior applications.
- General wood filling in windowsills and frames, doors and door frames, banisters, MDF, laminates etc.
- Repair of corner pieces in furniture
- Repair of wooden constructions, marine applications etc.
- Repairing chips and damage in parquet and laminate floors.

Limitations

Do not push mixture back into pack once mixed. Avoid contact with skin and eyes. Testing of small area for colour match is recommended. Discard mixed material after 10 minutes if unused.

As the manufacturer cannot know all the uses its products may be put to, it is the users responsibility to determine suitability for use. If in doubt, contact technical services for advice.

Surface Preparation

NOTE: If you intend to overstain the wood once filled ALWAYS CHOOSE THE COLOUR OF FILLER THAT NEAREST MATCHES THE WOOD YOU ARE FILLING, NOT THE STAIN YOU INTEND TO USE.

As the filler may absorb some stains at different rates to the surrounding timber, always test a small area first.

Before applying, ensure surfaces are clean, dry, sound and free from dust or any contaminants that may affect adhesion. Lightly sanding the area will improve adhesion. For areas damaged by wet rot, remove as much rotten wood as possible and harden the remaining area with EVERBUILD WET ROT WOOD HARDENER which will give a solid base for filling.

Application

Mix a golf ball volume of filler (approx 38mm diameter) and a 38mm strip of hardener into a homogeneous paste using the spatula provided. Press firmly into the surface requiring repair, leaving the filler slightly proud of the surface for sanding. Leave to dry for approximately 30 minutes before finishing by sanding/staining etc.

Specific Data

Base	2 Part system: Polyester resin and BPO Hardener
Consistency	Lightweight Stable paste
Curing System	Chemical reaction
Open Time	10 minutes maximum
Specific Gravity	ca. 1.0g/cm ³
Shrinkage	Nil at all depth
Working Temps	+5°C to +30°C. (Optimum 20°C).
Temperature Resistance	-20°C to +100°C.

Health & Safety

Consult MSDS for full list of hazards.

Storage

Store upright between 10 and 20°C in cool, dry conditions away from sources of ignition.

Shelf Life

12 months in original containers at stated storage temperatures.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.