

TECHNICAL DATA SHEET NO: 403

VERSION: 2/1ST MARCH 1999 PAGE: 1 OF 2 DATE OF ISSUE: 9/12/2014

EVERBUILD 403 CONCRETE HARDENER & DUSTPROOFER



Colour	Product Code	Pack Size	Box Qty
	CHD5L	5Ltr	4
-	CHDU25	25Ltr	1

Product Description

EVERBUILD CONCRETE HARDENER AND DUSTPROOFER is a concentrated silicate solution for direct application to concrete. Hardens and dustproofs the surface.

Benefits

- Internal and external use.
- Fast acting.
- Leaves a residual surface to prevent further dusting.
- Helps prevent bloom/efflorescence.

Areas For Use

As a dustproofer for new and old concrete/cement based floors, screeds and paving in factories, garages and domestic dwellings.

Limitations

- Only of use on cement containing surfaces
- Always wash down to remove unreacted material after use.
- Will not restore badly disintegrated concrete. Always carry out repairs prior to use using EVERBUILD EPOXY MORTAR GP.
- Do not treat concrete within 28 days of laying.

Application

Always read label before use and wear suitable protective equipment. Remove all surface debris and growth from the area to be treated. Repair any defects. Apply by brush or spray at a rate of 1 litre per 5 sq. meters. Work well into surface Apply a second coat after 24 hours. Allow second coat to dry for 24 hours then hose down entire area with cold, clean water to remove any unreacted surplus material. Further coats may be applied to exceptionally dusty floors.

Specific Data

Appearance	Clear solution	
Specific Gravity @ 20°C	1.2gcm ³	
Freezing point	0°c approx	
p.h	9 approx	
Drying Time	24 hours	
Coverage	1ltr will cover 5m ² of surface depending on surface, per coat	



TECHNICAL DATA SHEET NO: 403

PAGE: 2 OF 2

VERSION: 2/1ST MARCH 1999 DATE OF ISSUE: 9/12/2014

Health & Safety

Consult MSDS for full list of hazards.

Storage

Store at moderate temperatures in original containers. PROTECT FROM FROST.

Shelf Life

24 months from date of manufacture when stored according to manufacturers instructions.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.