

EVERBUILD CREOCOTE



Colour	Product Code	Pack Size	Box Qty
Light Brown	CREOLTBN4	4Ltr	4
	CREOLTBN20	20Ltr	1
Dark Brown	CREODKBN4	4Ltr	4
	CREODKBN20	20Ltr	1

Product Description

Creocote is an oil based wood treatment, effective when applied to exterior timbers such as garden sheds, fences and trellis work.

The oil based properties provide excellent surface water repellence and restricts weather damage. The product improves grain definition and exhibits the characteristic odour familiar to traditional Creosote users.

Benefits

- Oil based, excellent water repellency
- Improves Grain definition
- Ideal for use on external timbers.

Surface Preparation

Ensure that all timbers are structurally sound, dry and free from surface growths. Care should be taken to protect valuable plants and foliage during application. Children and pets should be kept away from treated timber until they are completely dry. Timber previously treated with Creosote, Creosote Substitute or a solvent based wood preservative will readily accept re-treatment with Creocote. Sealed or painted timbers must be stripped back to bare wood before coating with this product. The shade may vary from batch to batch and it is therefore recommended that containers with the same batch number are selected to ensure shade uniformity. Alternatively, premix different batches. The final shade is dependent upon the timber being treated and the previous covering applied. The colour will fade with time. To ensure suitability it is recommended that test patches are applied before general application.

Limitations

- Ready to use - do not dilute.
- For External use only
- Do not use on painted or sealed wooden surfaces.
- It is the user's responsibility to determine suitability for use. If in doubt, contact Technical Services Department for advice.

Surface Preparation

Creocote can be applied by brush, spray or dip methods. A deeper colour may be attained by applying further treatments. Apply liberally, soaking the timber to achieve test results. Always ensure that end-grain timbers are fully saturated. For timbers being set in the ground, apply Everbuild Bitumen Paints to protect against groundwater saturation.

Coverage Guide

Depending upon the texture and porosity of the timber to be treated, application of a single coat of Creocote will cover at the rate of 1 litre per 6 to 8 square meters.

Health & Safety

Consults MSDS for full list of hazards.

Storage

Store at moderate temperatures in original containers away from children.

Shelf Life

Use within 12 months.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.