

## D4 WOOD ADHESIVE



Colour	Product Code	Pack Size	Box Qty
Amber	D41	1Ltr	12
	D405	500ml	20

### Product Description

D4 Wood Adhesive is a solvent free industrial grade D4 wood adhesive based on the latest hybrid resin technology. The result of several years work, D4 Wood Adhesive provides the user with a waterproof D4 grade wood adhesive with none of the safety issues associated with conventional isocyanate containing (polyurethane) D4 grades.

D4 Wood Adhesive can be used internally and externally and gives a high strength, water, impact and temperature resistant bond that is usually stronger than the wood itself. Ideal for all general woodworking and joinery uses, assembly line work, RF/HF cure systems, wood on wood laminating, furniture assembly and household DIY use.

Dries clear. Easy water cleanup.

Conforms to the international standards EN 204 (D4) and WATT 91. Independent test certification is available on request.

### Benefits

- Excellent rate of bond strength development.
- D4 water resistance, suitable for constant water immersion.
- Interior/exterior use.
- Low timber staining characteristics - will not stain.
- Water based - environmentally friendly/easy clean up.
- Suitable for radio frequency cure.

### Areas For Use

- As a general woodworking/joinery adhesive.
- General assembly line work.
- RF/HF cure systems, wood on wood laminating, furniture assembly and household DIY use.

### Limitations

- Ensure wood doesn't contain excessive moisture (<15%)
- Not suitable for load bearing applications, use Everbuild 502 Wood Adhesive.
- Do not use at temperatures below 10°C.
- Note: drying time is extended at low temperatures.
- Clean excess adhesive off glue line after clamping before adhesive dries with a damp cloth..
- Sand off any excess adhesive before staining the wood.
- Ensure sufficient clamping pressure, especially important with radio frequency bonding.

- Use on Laminates: Only suitable for bonding small porous laminate strips. Do not use on non-porous or large areas of laminate. Use CONTACT ADHESIVE.
- Because of the varied nature of wood components, e.g. area of growth, type of pre-treatment etc, unpredictable discolouration may occur on different types of wood such as cherry, beech and others. In certain oaks, iron and tannin can also give this effect. We recommend you test compatibility before carrying out large scale manufacture.

### Surface Preparation

All surfaces must be clean, dry and free from grease.

### Application

Apply adhesive **thinly** to both surfaces. Do not over apply as this will slow down cure. Clamp surfaces together until adhesive dries. (off in 1-2 hours: full strength 8 hours). Support until fully cured (8 hours at 20°C).

When fitting dowels, the adhesive should be applied to the holes.

- Suitable for radio frequency curing.

### Specific Data

Total Solids (%)	40 – 48%
Viscosity @ 23°C Brookfield RTV 5/20 Poise mPa.s	80 – 200 10000 - 20000
pH	2.5 – 3.5
Minimum Film Forming Temperature (°C)	Approx 3
High Temperature Stability (1 week @ 50°C)	Stable
Specific Gravity	1.07 (dispersion)

### Health & Safety

Consult MSDS for full list of hazards.

### Storage

To ensure safe storage of product, containers should be well sealed to prevent evaporation of water and the formation of skin on the surface. The emulsion must be stored at a temperature above freezing. A temperature of 5-25°C for not more than six months is recommended. Higher temperatures will affect quality and cause the formation of crusts and skins, especially if the containers are not tightly closed or subjected to direct sunlight for long periods.

If these conditions cannot be met, please refer to our Technical Service Department who will advise on storage stability.

### Shelf Life

6 months from date of manufacture in original unopened containers.

*The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.*