



SAFETY DATA SHEET

FEBTANK SUPER

Page 1

Issued: 11/03/2009

Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: FEBTANK SUPER
Product code: FBTANKSGY/WE
Company name: EVERBUILD BUILDING PRODUCTS LTD
SITE 41, KNOWSTHORPE WAY
CROSS GREEN INDUSTRIAL ESTATE
LEEDS
WEST YORKSHIRE
LS9OSW
ENGLAND
Tel: 0044 113 240 3456
Fax: 0044 113 240 0024
Emergency tel: 0044 113 240 3456 (office hours only)
Email: paul@everbuild.co.uk

2. HAZARDS IDENTIFICATION

Main hazards: Risk of serious damage to eyes. Contact with wet cement, wet concrete or wet mortar may cause irritation, dermatitis or burns. Contact between cement powder and body fluids (eg sweat and eye fluid) may also cause skin and respiratory irritation, dermatitis or burns. **Other hazards:** Contains Chromium VI. May produce an allergic reaction

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: ORDINARY PORTLAND CEMENT 10-30%
CAS: 65997-15-1
[Xi] R41; [-]; [-]
• HIGH ALUMINA CEMENT 1-10%
CAS: 65997-16-2
[Xi] R41; [-]; [-]

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.
Eye contact: There may be irritation and redness. The eyes may water profusely.
Ingestion: There may be soreness and redness of the mouth and throat.
Inhalation: Exposure may cause coughing or wheezing.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.
Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

[cont...]

SAFETY DATA SHEET

FEBTANK SUPER

Ingestion: Wash out mouth with water. Consult a doctor.**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.**5. FIRE-FIGHTING MEASURES****Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used.**Exposure hazards:** In combustion emits toxic fumes.**Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.**6. ACCIDENTAL RELEASE MEASURES****Personal precautions:** Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Do not create dust.**Environmental precautions:** Do not discharge into drains or rivers.**Clean-up procedures:** Transfer to a closable, labelled salvage container for disposal by an appropriate method.**7. HANDLING AND STORAGE****Handling requirements:** Avoid direct contact with the substance. Avoid the formation or spread of dust in the air.**Storage conditions:** Keep container tightly closed. Store in original containers between +5 and +25°C. Storage outside these parameters will dramatically reduce shelf life and invalidates all product warranties.**Suitable packaging:** Must only be kept in original packaging.**8. EXPOSURE CONTROLS / PERSONAL PROTECTION****Hazardous ingredients:** ORDINARY PORTLAND CEMENT
WEL (8 hr TWA): 10mg/m³**Respirable dust:** ORDINARY PORTLAND CEMENT
WEL (8 hr TWA): 5mg/m³**Engineering measures:** Ensure there is sufficient ventilation of the area.**Respiratory protection:** Respiratory protective device with particle filter. Self-contained breathing apparatus must be available in case of emergency.**Hand protection:** Protective gloves.**Eye protection:** Safety glasses. Ensure eye bath is to hand.**Skin protection:** Protective clothing.**9. PHYSICAL AND CHEMICAL PROPERTIES****State:** Powder**Colour:** Coarse Grey or White Powder**Odour:** Odourless**Evaporation rate:** Negligible**Solubility in water:** Slightly soluble**Relative density:** 1.45

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Moist air. Humidity.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Chronic toxicity: May cause sensitisation by skin contact.

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Persistence and degradability: No data available.

Bioaccumulative potential: No data available.

Other adverse effects: No data available.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Dispose of according to local or national legislation

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: Not Classified.

IMDG / IMO

UN no: Not Classified.

IATA / ICAO

UN no: Not Classified.

15. REGULATORY INFORMATION

Hazard symbols: Irritant.



Risk phrases: R41: Risk of serious damage to eyes.

Contact with wet cement, wet concrete or wet mortar may cause irritation, dermatitis or burns.

Contact between cement powder and body fluids (eg sweat and eye fluid) may also cause skin and respiratory irritation, dermatitis or burns.

SAFETY DATA SHEET

FEBTANK SUPER

Safety phrases: S2: Keep out of the reach of children.
S22: Do not breathe dust.
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S28: After contact with skin, wash immediately with plenty of water.
S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.
S46: If swallowed, seek medical advice immediately and show this container or label.

Precautionary phrases: Contains chromium (VI). May produce an allergic reaction.

Haz. ingredients (label): ORDINARY PORTLAND CEMENT; HIGH ALUMINA CEMENT

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.3: R41: Risk of serious damage to eyes.
Contact with wet cement, wet concrete or wet mortar may cause irritation, dermatitis or burns.
Contact between cement powder and body fluids (eg sweat and eye fluid) may also cause skin and respiratory irritation, dermatitis or burns.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.