

EVERBUILD FILL & SKIM



Colour	Product Code	Pack Size	Box Qty
White	FILLSKIM5	5LTR	1

Product Description

FILL AND SKIM is revolutionary new ready mixed plaster substitute, formulated using lightweight polymer spheres, to produce an easy to spread and smooth product which enables all tradesmen and DIY enthusiasts to produce a quality finish, normally only associated with a time served plasterer. FILL AND SKIM dries to a hard but flexible finish and is therefore suitable for wall or ceiling application and will fill holes down to 25mm in one application.

FILL AND SKIM is the ideal choice for covering textured paint surfaces and for restoring old pitted/uneven plastered walls/ceilings in just one quick application. FILL AND SKIM is also the ideal choice for electricians, plumber, joiners and general builders as a one coat patching plaster for small repair jobs, e.g. over recessed cable trunking and around holes in walls where piping/sockets have been installed.

Once, dry, FILL AND SKIM will not shrink, sag or crack and is ready to paint or paper 24 hours after application.

FILL AND SKIM finishes smooth and requires little or no sanding. FILL AND SKIM can be used for internal repairs over plaster, wood, brick, stone and rendering.

Surface Preparation

Ensure the surface is clean, dry, sound and free from loose material or mould. Very friable surfaces should first be treated with EVERBUILD STABILISING SOLUTION and allowed to dry. Nail or screw heads must be coated in oil based primer. Stain marks should be treated with EVERBUILD STAIN BLOCK. Glossy surfaces should be rubbed down to provide a key. Holes deeper than 25mm should be filled with a suitable filler (e.g. EVERBUILD ONE STRIKE) and allowed to dry. Textured paints/surfaces must be lightly sanded to remove peaks.

Application

Stir FILL AND SKIM to a smooth paste. If product is too dry, add a few drops of water and re-stir. Load smoothing blade (provided with this product) using a suitable spatula. Work over no greater than 0.5m² at a time towards centre of area to be coated. Apply in smooth curves ensuring even pressure and cover area. Work back with smoothing trowel over any ridges to smooth flat with rest of surface. Repeat over rest of area, covering 0.5m² at a time and "blending in" each area.

When filling a large surface area, it may not always be possible to achieve a completely level finish. However, FILL AND SKIM is very easy to sand if necessary.

Deep holes up to 25mm can be filled in one application with no need to build up in several layers.

Coverage: Approx 0.75m²/Litre at 6mm depth.

FINISHING: FILL AND SKIM can be papered over, or painted with water or oil based paints as soon as the product is dry – approximately 24 hours – depending on depth and drying conditions. If priming is required, follow paint manufacturers instructions.

Limitations

- Do not use in areas subject to continuous water immersion.
- Do not use externally.
- Do not use for structural repairs.
- Do not allow water contact within 24 hours of application.
- Absorption of paint on the filler may be different to surrounding areas. If filler shows through after painting, simply apply further coats.

Health & Safety

Consult MSDS for full list of hazards.

Storage

Store in cool dry conditions between +5 and +25°C. Storage outside these parameters will dramatically reduce shelf life. Protect from frost.

Shelf Life

Use within 12 months.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.