

EVERBUILD FOREVER WHITE POWDER WALL TILE GROUT



Colour	Product Code	Pack Size	Box Qty
Arctic White	FWPOWGROUT1	1.2kg box	10
Arctic White	FWPOWGROUT3	3kg bag	1
Arctic White	FWPOWGROUT10	10kg bag	1

Product Description

With Mould Shield[®] one of the world's leading anti-bacterial solutions integrated into the manufacturing process, Forever White Powder Wall Tile Grout is guaranteed to stop mould, mildew and bacterial growth.

Mould Shield[®] actively prevents the growth of bacteria, mildew and black mould that are commonly found in areas of high humidity.

Forever White Powder Wall Tile Grout is independently tested and certified by a NAMMAS accredited microbiological laboratory to show no mould growth after more than 10 Years simulated ageing.

Copies of test data are available upon request.

Forever White Powder Wall Tile Grout dries to an extra brilliant white finish

Forever White Powder Wall Tile Grout is a cement based powdered grouting compound with added PVA to promote adhesion and water repellents to shed water. Simply mix with water to give a pure white paste.

Benefits

- Excellent water resistance.
- Dries brilliant white.
- Contains Mould Shield[®] - prevents mould growth.
- Can be used on wall joints up to 3mm.

Areas for Use

- Kitchen/Bathroom walls.
- Shower areas.
- Work tops subject to water contact

Limitations

- Unsuitable for floors.
- Always mix with clean fresh water. Allow adhesive to dry before grouting. Protect from running water and frost until completely dry. Do not use where application would trap moisture within the substrate.
- Tiles must be left for at least 24hr (3 days on non porous surfaces) for the adhesive to dry before grouting; longer at low temperatures. Grouting too early will cause a discolouration of the grout which is normally Arctic White in colour.
- As the manufacturer cannot know all the uses its products may be put to, it is the user's responsibility to determine suitability for use. If in doubt, contact Technical Services department for advice or refer to Technical Data Sheet. In all circumstances, the manufacturer's liability is limited to the value of the manufacturer's product purchased.

Application

All surfaces must be clean, dry and free from contaminants such as adhesive, paint etc. Tiles must be left for at least 24hr (3 days on non porous surfaces) for the adhesive to dry before grouting. Mix approximately 2 parts powder to 1 part water. Mix to a smooth lump free paste. Allow to stand 10 minutes before grouting, then re-stir.

Apply by cloth or squeegee. Push grout well into joints so no voids remain behind. Remove excess grout with a damp cloth before it dries.

Protect all grouted areas from running water and frost until the grout is completely dry.

Health & Safety

Consult MSDS for full list of hazards.

Storage

Store in cool dry conditions. AVOID MOISTURE

Shelf Life

12 months when stored in original unopened containers

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.