



SAFETY DATA SHEET

JETCEM

Page 1
Issued: 03/11/2008
Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: JETCEM
Product code: JETCEM
Company name: EVERBUILD BUILDING PRODUCTS LTD
SITE 41, KNOWSTHORPE WAY
CROSS GREEN INDUSTRIAL ESTATE
LEEDS
WEST YORKSHIRE
LS9OSW
ENGLAND
Tel: 0044 113 240 3456
Fax: 0044 113 240 0024
Emergency tel: 0044 113 240 3456 (office hours only)
Email: pault@everbuild.co.uk

2. HAZARDS IDENTIFICATION

Main hazards: Risk of serious damage to eyes.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: ORDINARY PORTLAND CEMENT 30-50%
CAS: 65997-15-1
[Xi] R41; [-]; [-]
• HIGH ALUMINA CEMENT 1-10%
CAS: 65997-16-2
[Xi] R41; [-]; [-]

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be mild irritation at the site of contact.
Eye contact: There may be irritation and pain.
Ingestion: There may be soreness and redness of the mouth and throat.
Inhalation: There may be coughing and a sore throat.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash immediately with plenty of soap and water.
Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.
Ingestion: Wash out mouth with water. Consult a doctor.
Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

[cont...]

Protection of fire-fighters: Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Do not create dust.

Clean-up procedures: Clean spillage area thoroughly with plenty of water.

7. HANDLING AND STORAGE

Handling requirements: Avoid creation of dust cloud

Storage conditions: Avoid contact with water or humidity.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: ORDINARY PORTLAND CEMENT

WEL (8 hr TWA): 10mg/m³

Respirable dust: ORDINARY PORTLAND CEMENT

WEL (8 hr TWA): 5mg/m³

Engineering measures: Non required

Respiratory protection: Respiratory protection not required. in normal use.

Hand protection: Protective gloves.

Eye protection: Safety glasses.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Solid

Colour: Grey

Odour: Odourless

Solubility in water: Miscible

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Moist air.

Materials to avoid: Acids. Oxidising agents.

11. TOXICOLOGICAL INFORMATION

12. ECOLOGICAL INFORMATION

Mobility: Non-volatile.

Persistence and degradability: Biodegradable.

Bioaccumulative potential: No bioaccumulation potential.

Other adverse effects: Negligible ecotoxicity.

13. DISPOSAL CONSIDERATIONS

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: Not Classified.

IMDG / IMO

UN no: Not Classified.

IATA / ICAO

UN no: Not Classified.

15. REGULATORY INFORMATION

Hazard symbols: Irritant.



Risk phrases: R41: Risk of serious damage to eyes.

Safety phrases: S2: Keep out of the reach of children.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S39: Wear eye / face protection.

S46: If swallowed, seek medical advice immediately and show this container or label.

Haz. ingredients (label): ORDINARY PORTLAND CEMENT; HIGH ALUMINA CEMENT

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.3: R41: Risk of serious damage to eyes.

Contact with wet cement, wet concrete or wet mortar may cause irritation, dermatitis or burns.

Contact between cement powder and body fluids (eg sweat and eye fluid) may also cause skin and respiratory irritation, dermatitis or burns.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.