

EVERBUILD JETCEM QUICK SETTING PATCHING PLASTER

Colour	Product Code	Pack Size	Box Qty
Beige	JETPATCH6	6KG	2

Product Description

Jetcem Quick Setting Patching Plaster is a high strength plaster in powder form which easily mixes with water to form a creamy lump free paste that is the ideal choice for most patching repairs. The product dries hard in 1 hour to a smooth finish which can be further sanded if desired. With added PVA powder, this product will not shrink or crack and is strong enough to accept nails or screws.

Benefits

- Dries in 1 hour.
- Easy mixing, just add water.
- Adheres to most common building surfaces.

Areas for Use

- Plaster
- Plasterboard
- Brick
- Render
- Wood
- Stone and most other building materials

Limitations

- For holes deeper than 1 ½ inch, apply in layers and allow to dry before applying second layer.
- Do not add further water once the plaster has started to go off. Remix a fresh batch.
- Allow to fully dry before over coating.
- Only use on porous surfaces. Do not apply over plastics, sealants, paints or primers.
- Wood repairs – do not use in areas where impact resistance or flexibility is required, e.g. door surrounds. Use EVERBUILD HIGH PERFORMANCE WOOD FILLER.
- Do not use below 10°C.
- It is always the user's responsibility to determine suitability of use. If in doubt, request technical data or contact technical services.

Surface Preparation

Before applying, ensure surfaces are clean, sound and free from dust, crumbly material or any contaminants, which may affect adhesion.

Cover nail or screw heads with oil based paints and allow to dry.

Dampen all porous surfaces to improve adhesion.

Application

- Always use a clean mixing vessel and add approx. 2 ½ parts powder to one part by volume clean cold water and mix immediately to a smooth paste. The mixed plaster will remain workable for 30-40 minutes.
- Smooth the Jetcem Patching Plaster over the repair with a trowel.
- Finish with a wet knife, if sanding is desired fill the hole slightly proud to allow for sanding down.

FINISHING

- Jetcem Patching Plaster is normally sandable and overpaintable after approximately one hour.
- Once dry, sand to a smooth finish
- Jetcem Patching Plaster may be painted or papered when dry.

Health & Safety

Consult MSDS for full list of hazards.

Storage

Store in cool dry conditions between + 5°C and 25°C. Storage outside these parameters will significantly reduce shelf life.

Shelf Life

12 months in original unopened bag. This will reduce significantly once opened.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.