

**EVERBUILD JETCEM WATERPROOFING RAPID SETTING CEMENT**

Colour	Product Code	Pack Size	Box Qty
Grey	JETWAT3	3KG	4

**Product Description**

Jetcem Waterproofing Rapid Setting Cement is a cement based mix, formulated specifically for water resistance and is designed to set hard in about 30minutes.

**Benefits**

- Rapid setting (30 minutes, depending on ambient temperature and conditions).
- Easy mixing, just add water.
- Waterproof once cured.

**Areas for Use**

- Repairs to cracks and holes in structures subject to permanent water immersion
- Patching repairs to tanking & water retaining structures
- Repairs to ponds and pools
- Ideal for repairs to steps in basements, and areas susceptible to damp
- Seal and joint drains and pipes
- Filling around pipes, through gaps
- Bedding sanitary ware (pedestal, toilets etc)

**Limitations**

- This product should not be used for load bearing applications. Use EVERBUILD ANCHOR SET.
- Do not use on holes deeper than 25mm. large voids may be filled with Fix and Fill Expanding foam then finished with Jetcem Waterproofing cement once cured.
- Repairs to ponds and pools must be sealed with a suitable paint before re-filling.
- Do not use where chemical resistance is required. Use EVERBUILD EPOXY MORTAR GP
- It is always the user's responsibility to determine suitability of use. If in doubt, request technical data or contact Technical Services department.

**Surface Preparation**

Before applying, ensure surfaces are clean, sound and free from dust, crumbly material or any contaminants, which may affect adhesion.

**Application**

- Thoroughly wet surfaces to improve adhesion.
- Using clean, dry tools, mix Jetcem Waterproofing Cement with clean, cold water to a smooth paste.
- IMPORTANT – Do not mix more cement than can be used in 5-10 minutes.

- Apply the mixture immediately with a trowel or knife, working well into area to be repaired.
- Press the cement into the repair with a trowel or filling knife.
- Level with surrounding area before mixture starts to set, usually within 10 minutes.
- Once the product begins to stiffen, throw away the residue. DO NOT ADD FURTHER WATER TO THE MIX. THIS WILL DESTROY STRENGTH

#### **Health & Safety**

Consult MSDS for full list of hazards.

#### **Storage**

Store in cool dry conditions between + 5°C and 25°C. Storage outside these parameters will significantly reduce shelf life.

#### **Shelf Life**

12 months in original unopened bag. This will reduce significantly once opened.

*The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.*