

LUMBERJACK 650 FLOORING ADHESIVE STANDARD

Page: 1

Compilation date: 24/3/11

Revision No: 2

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

# Product name: LUMBERJACK 650 FLOORING ADHESIVE STANDARD

Product code: LJ65014

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

# 1.3. Details of the supplier of the safety data sheet

Company name: EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY

CROSS GREEN INDUSTRIAL ESTATE

LEEDS

- WEST YORKSHIRE
- LS9OSW
- ENGLAND
- Tel: 0044 113 240 3456
- Fax: 0044 113 240 0024
- Email: pault@everbuild.co.uk

## 1.4. Emergency telephone number

Emergency tel: 0044 113 240 3456 (office hours only)

# Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification under CHIP: This product has no classification under CHIP.

Classification under CLP: This product has no classification under CLP.

2.2. Label elements

Label elements under CHIP:

Hazard symbols: No significant hazard.

Precautionary phrases: Contains n-(2-aminoethyl)-3-aminopropyltrimethoxysilane, hindered amine light

stabiliser. May produce an allergic reaction.

2.3. Other hazards

PBT: This substance is not identified as a PBT substance.

# Section 3: Composition/information on ingredients

3.2. Mixtures

# LUMBERJACK 650 FLOORING ADHESIVE STANDARD

#### Hazardous ingredients:

# PPG 1000

EINECS	CAS	CHIP Classification	CLP Classification	Percent
-	-	Xn: R22	-	10-30%
TRIMETHOXY	VINYLSILANE			
220-449-8	2768-02-7	-: R10; Xn: R20	Acute Tox. 4: H332; Flam. Liq. 3: H226	1-10%
HINDERED AM	IINE LIGHT STA	BILISER		
-	-	Sens.: R43; N: R50/53	-	<1%

# Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

# 4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

# Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

# 5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

#### Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid.

# LUMBERJACK 650 FLOORING ADHESIVE STANDARD

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

# Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

#### 7.3. Specific end use(s)

Specific end use(s): No data available.

## Section 8: Exposure controls/personal protection

#### 8.1. Control parameters

Workplace exposure limits: Not applicable.

### 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.
Respiratory protection: Respiratory protection not required.
Hand protection: Protective gloves.
Eye protection: Safety glasses. Ensure eye bath is to hand.
Skin protection: Protective clothing.

# Section 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

State:LiquidColour:VariousOdour:Sweet-smellingViscosity:Highly viscousBoiling point/range°C:>100Relative density:~1.6

Flash point°C: >93 VOC g/I: 23.6

# LUMBERJACK 650 FLOORING ADHESIVE STANDARD

#### 9.2. Other information

### Section 10: Stability and reactivity

#### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

#### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

#### **10.6.** Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

### Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values: Not applicable.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

### Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: Not applicable.

# 12.2. Persistence and degradability

Persistence and degradability: No data available.

# 12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

# LUMBERJACK 650 FLOORING ADHESIVE STANDARD

#### 12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

### 12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

# Section 13: Disposal considerations

# 13.1. Waste treatment methods

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

### Section 14: Transport information

Transport class: This product is not classified for transport.

# Section 15: Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

# Section 16: Other information

Other information				
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No			
	453/2010.			
	* indicates text in the SDS which has changed since the last revision.			
Phrases used in s.2 and 3:	H226: Flammable liquid and vapour.			
	H332: Harmful if inhaled.			
	R10: Flammable.			
	R20: Harmful by inhalation.			
	R22: Harmful if swallowed.			
	R43: May cause sensitisation by skin contact.			
	R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the			
	aquatic environment.			
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive			
	and shall be used only as a guide. This company shall not be held liable for any			
	damage resulting from handling or from contact with the above product.			