



SAFETY DATA SHEET
LUMBERJACK WOOD PRESERVER

Page: 1

Compilation date: 21/3/11

Revision No: 4

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: LUMBERJACK WOOD PRESERVER **Product**
code: LJ - ALL COLOURS AND

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY
CROSS GREEN INDUSTRIAL ESTATE
LEEDS
WEST YORKSHIRE
LS9OSW
ENGLAND

Tel: 0044 113 240 3456

Fax: 0044 113 240 0024

Email: pault@everbuild.co.uk

1.4. Emergency telephone number

Emergency tel: 0044 113 240 3456 (office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: -: R52/53

Most important adverse effects: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Classification under CLP: This product has no classification under CLP.

2.2. Label elements

Label elements under CHIP:

Hazard symbols: No significant hazard.

Risk phrases: R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases: S2: Keep out of the reach of children.

S35: This material and its container must be disposed of in a safe way.

S57: Use appropriate container to avoid environmental contamination.

Precautionary phrases: Use biocides safely. Always read the label and product information before use.
Contains propiconazole. May produce an allergic reaction.

[cont...]

2.3. Other hazards

SAFETY DATA SHEET
LUMBERJACK WOOD PRESERVER

Page: 2

PBT: This substance is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

PROPICONAZOLE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
262-104-4	60207-90-1	Xn: R22; Sens.: R43; N: R50/53	Acute Tox. 4: H302; Skin Sens. 1: H317; Aquatic Chronic 1: H410; Aquatic Acute 1: H400	<1%

IPBC

-	55406-53-6	Xn: R20; Xn: R22; Xi: R41; N: R50	-	<1%
---	------------	-----------------------------------	---	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

[cont...]

SAFETY DATA SHEET
LUMBERJACK WOOD PRESERVER

Page: 3

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air. Do not handle in a confined space. Avoid direct contact with the substance.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: Not applicable.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure all engineering measures mentioned in section 7 of SDS are in place.

Respiratory protection: Respiratory protective device with particle filter. in normal use. Respiratory protection not required. Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour concentration is above OES or if ventilation is poor

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

[cont...]

SAFETY DATA SHEET
LUMBERJACK WOOD PRESERVER

Page: 4

Colour: Various

Odour: Barely perceptible odour

Evaporation rate: Moderate

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Also soluble in: Most organic solvents.

Viscosity: Non-viscous

Kinematic visc. 40°C (mm²/s): <5cSt

Viscosity test method: Kinematic viscosity in 10-6 m2/s at 40°C (ISO 3104/3105)

Boiling point/range°C: approx 100°C

Flash point°C: >93

Vapour pressure: 4.6

Relative density: 1.00-1.01

pH: 6.5-8.5

VOC g/l: 0

9.2. Other information

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Direct sunlight.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values: Not applicable.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

[cont...]

SAFETY DATA SHEET
LUMBERJACK WOOD PRESERVER

Page: 5

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: Not applicable.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Harmful to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal of packaging: Clean with water. Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3082

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(PROPICONAZOLE; IPBC)

14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: III

[cont...]

SAFETY DATA SHEET
LUMBERJACK WOOD PRESERVER

Page: 6

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E Transport

category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: H302: Harmful if swallowed.

H317: May cause an allergic skin reaction.

H410: Very toxic to aquatic life with long lasting effects.

R20: Harmful by inhalation.

R22: Harmful if swallowed.

R41: Risk of serious damage to eyes.

R43: May cause sensitisation by skin contact.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R50: Very toxic to aquatic organisms.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

SAFETY DATA SHEET
LUMBERJACK WOOD PRESERVER

Page: 7
[final page]