

### SAFETY DATA SHEET

### LUMBERJACK TRIPLE ACTION WOOD TREATMENT

Page 1

Issued: 9/9/08

Revision No: 2

#### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

LUMBERJACK TRIPLE ACTION WOOD TREATMENT

**Product name:** 

**Product code:** LJUN - ALL SIZES

Use of substance / preparation:

Timber Preservative

Company name: EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY

CROSS GREEN INDUSTRIAL ESTATE

**LEEDS** 

WEST YORKSHIRE

LS9OSW ENGLAND

Tel: 0044 113 240 3456 Fax: 0044 113 240 0024

Emergency tel: 0044 113 240 3456 (office hours only)

Email: pault@everbuild.co.uk

## 2. HAZARDS IDENTIFICATION

Main hazards: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

**Hazardous ingredients:** PROPICONAZOLE <1%

EINECS: 262-104-4 CAS: 60207-90-1 [Xn] R22; [Sens.] R43; [N] R50/53

• M-PHENOXYBENZYL

3-(2,2-DICHLOROVINYL)-2,2-DIMETHYLCYCLOPROPANECARBOXYLATE <1%

EINECS: 258-067-9 CAS: 52645-53-1 [Xn] R20/22; [Sens.] R43; [N] R50/53

## 4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

**Inhalation:** No symptoms.

## 4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes.

[cont...]

#### SAFETY DATA SHEET

## LUMBERJACK TRIPLE ACTION WOOD TREATMENT

**Ingestion:** Wash out mouth with water.

Inhalation: Consult a doctor. Remove casualty from exposure ensuring one's own safety whilst doing so.

### 5. FIRE-FIGHTING MEASURES

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used.

**Exposure hazards:** In combustion emits toxic fumes.

**Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin

and eyes.

### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:** Refer to section 8 of SDS for personal protection details.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by

an appropriate method.

### 7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.

Do not handle in a confined space. Avoid direct contact with the substance.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Engineering measures:** 

Ensure there is sufficient ventilation of the area. Ensure all engineering measures mentioned in section

7 of SDS are in place.

**Respiratory** Respiratory protective device with particle filter. Gas/vapour filter, type A: organic vapours

**protection:** (EN141). if spraying

Hand protection: Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid Colour: Various

Odour: Barely perceptible odour

Evaporation rate: Moderate

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Soluble

Also soluble in: Most organic solvents.

Viscosity: Non-viscous

Viscosity value: <5cSt

**Boiling point/range°C:** approx 100°C

Flash point°C: >60 Vapour pressure: 4.6

[cont...]

### SAFETY DATA SHEET

LUMBERJACK TRIPLE ACTION WOOD TREATMENT

Relative density: 1.00-1.01

**pH:** 6.5-8.5

**VOC g/l:** 0

# 10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions. Stable at room temperature.

Conditions to avoid: Heat. Direct sunlight.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

## 11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: M-PHENOXYBENZYL

3-(2,2-DICHLOROVINYL)-2,2-DIMETHYLCYCLOPROPANECARBOXYLATE

ORL MUS LD50 424 mg/kg ORL RAT LD50 383 mg/kg SKN RAT LD50 1750 mg/kg

**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

## 12. ECOLOGICAL INFORMATION

**Mobility:** Readily absorbed into soil.

**Persistence and degradability:** Biodegradable. **Bioaccumulative potential:** No data available.

Other adverse effects: Very toxic to aquatic organisms.

# 13. DISPOSAL CONSIDERATIONS

**Disposal operations:** Dispose of according to local or national legislation

**Disposal of packaging:** Dispose of in a regulated landfill site or other method for hazardous or toxic

wastes. **NB:** The user's attention is drawn to the possible existence of regional or

national regulations regarding disposal.

# 14. TRANSPORT INFORMATION

## ADR / RID

**UN no:** 3082 **ADR Class:** 9

Packing group: III Classification code: M6

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Labelling: 9 Hazard ID no: 90



### IMDG / IMO

3082

 $\begin{array}{c|cccc} \textbf{UN no:} & \textbf{Class:} & 9 \\ \textbf{Packing group:} & \textbf{III} & \textbf{EmS:} & \textbf{F-A,S-F} \\ \end{array}$ 

[cont...]

### SAFETY DATA SHEET

## LUMBERJACK TRIPLE ACTION WOOD TREATMENT

Marine pollutant: .

Labelling: 9

IATA / ICAO

3082

UN no:

Class: 9

Packing group: III

Packing instructions: 914

Labelling: 9

15. REGULATORY INFORMATION

Hazard symbols: Dangerous for the environment.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

Risk phrases:

environment.

Safety phrases:

S29: Do not empty into drains.

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

S2: Keep out of the reach of children.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

S28: After contact with skin, wash immediately with plenty of soap and water. S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

**Precautionary** phrases:

Use biocides safely. Always read the label and product information before use.

Contains propiconazole, m-phenoxybenzyl

3-(2,2-dichlorovinyl)-2,2-dimethylcyclopropanecarboxylate. May produce an allergic reaction.

M-PHENOXYBENZYL

3-(2,2-DICHLOROVINYL)-2,2-DIMETHYLCYCLOPROPANECARBOXYLATE

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all

applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Other information: HSE No.: 8529 Risk

phrases used in s.3: R22: Harmful if swallowed.

## **SAFETY DATA SHEET**

# LUMBERJACK TRIPLE ACTION WOOD TREATMENT

R43: May cause sensitisation by skin contact.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R20/22: Harmful by inhalation and if swallowed.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall

be used only as a guide. This company shall not be held liable for any damage resulting from

handling or from contact with the above product.

[final page]