

TECHNICAL DATA SHEET NO: XT441 VERSION: 1/9/9/11 PAGE: 1 OF 2 DATE OF ISSUE: 9/12/2014

# **EVERBUILD XT44 MAINTENANCE SPRAY**



Colour	<b>Product Code</b>	Pack Size	<b>Box Qty</b>
-	MULTI	400ML	12

### **Product Description**

EVERBUILD XT44 MAINTENANCE SPRAY is an all-purpose maintenance spray with hundreds of uses in and around the home, garage, and workshop and in industry.

### **Benefits**

- Fast acting penetrates quickly and deeply to release locked parts
- Displaces moisture.
- Protects metal surfaces to prevent rust.

## **Areas For Use**

- Penetrates rusted parts and fastenings to assist dismantling.
- Lubricates locks, tools and hinges
- Stops squeaks on metal, wood and plastic
- Protects metals from rusting, especially when stored in damp areas.
- Displaces water can be used to assist starting wet petrol engines and damp ignition systems.

# Limitations

CAUTION- EXTREMELY FLAMMABLE. Do not spray directly onto incandescent or hot surfaces.

#### **Application**

Shake can well and spray directly onto item to be treated. For precise applications, fit straw to help direct spray. Badly rusted or corroded fastenings may require two or three applications., allowing one hour between applications.

#### **Specific Data**

Specific Bata	
Appearance	Dark Brown Liquid
Odour	Oil / Solvent
Melting Point	Not det.
Flashpoint	<0°C
Solubility	Immiscible
VOC Content	High – not specifically given
Auto IGN	N/D



TECHNICAL DATA SHEET NO: XT441 VERSION: 1/9/9/11 PAGE: 2 OF 2 DATE OF ISSUE: 9/12/2014

Explosion Limits	Not given
Density	0.81 g/cm <sup>3</sup>
рН	N/A
Vapour Density	Heavier than air.

### **Health & Safety**

Consult MSDS for full list of hazards.

### **Storage**

Store in cool dry conditions between + 5°C and 25°C. Avoid heat and static discharges. Pressurized container – Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn even after use.

#### **Shelf Life**

12 months from date of manufacture.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.