

EVERBUILD OPTIMIX CEMENT COLOURANT



Colour	Product Code	Pack Size	Box Qty
	OPTITONEBK02	250ml	12
Black	OPTITONEBK1	1ltr	10
Brown	OPTITONEBN1	1ltr	10
Red	OPTITONERD1	1ltr	10
Yellow	OPTITONEYW02	250ml	12
	OPTITONEYW1	1ltr	10

Product Description

OPTIMIX CEMENT COLOURANT is a concentrated one shot cement colourant that provides a permanent colour to all types of mortars, rendering, concrete and pointing. The liquid disperses evenly through the mix, to give a uniform shade for each mix batch. Shading can be adjusted to give a wide variety of colour depths.

Benefits

- Concentrated formula 1ltr is equivalent to 5ltrs of standard colourant
- Easy to use gauged bottle.
- Less “messy” than powdered equivalents.
- Quickly disperses in the mix.

Areas For Use

Mortars, renders and screeds.
Pointing mortars
Colouring cement based tile grouts.

Limitations

- Do not use in structural concrete.
- Do not use in lime based mixes.
- Always use same batches of sand/cement. This will avoid any differences showing through over large areas.
- It is the users responsibility to determine suitability for use. If in doubt contact Technical Services Department for further advice.

Application

Shake bottle well before use. Push the lid downwards and twist anti-clockwise to remove. Squeeze the sides of the bottle to fill the measuring cup to the required dose (25ml per 10kg of Mortar).

Specific Data

Appearance	Coloured liquid
Specific Gravity @ 20°C	1.1-1.35g/cm ³
Solids Content (%)	37-42
Usage	25ml per 10kg of mortar
pH	6-9

Health & Safety

Consult MSDS for full list of hazards.

Storage

Store in original unopened containers between 5 and 40°C.

Shelf Life

12 months from date of manufacture.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.