

FLUE JOINTING COMPOUND



Colour	Product Code	Pack Size	Box Qty
-	PCFJC05	500GM	12
	PCFJC1	1KG	12
	PCFJC2	2KG	4

Product Description

FLUE JOINTING COMPOUND is a ready mixed paste/putty for sealing metal flue joints in domestic or industrial applications where the flue temperature does not exceed 200°C. FLUE JOINTING COMPOUND does not harden completely and remains flexible to accommodate movement.

Benefits

- Ready mixed formula.
- Temperature resistant up to 200°C.
- Internal or external use.
- Non flammable.

Areas For Use

- Jointing metal flues.
- As a general sealing compound.
- Low pressure air ducts.
- Chasing pipes through brickwork.

Limitations

- Do not use externally when rain is imminent or on damp surfaces.
- Do not alter consistency
- Do not use in excess of 200 degrees C.

Surface Preparation

For maximum adhesion ensure all surfaces are free from all loose dirt and contaminants i.e. rust, soot, dust etc.

Application

FLUE JOINTING COMPOUND should be used straight from the tub. Apply by hand or putty knife working well into the joint to completely fill it. When connecting flue pipes, wrap glass fibre rope around the spigot end before inserting to facilitate a tighter joint.

Specific Data

Appearance	Thick paste
SG @ 20°C	1.8 gcm ³ (approx)
Application Temp	5°C to 60°C
Service Temp	-10 to 200°C
Coverage	1kg will cover approx 3 linear metres of joint.

Health & Safety

Consult MSDS for full list of hazards.

Storage

Store at moderate temperatures in original containers. Keep out of direct sunlight.

Shelf Life

Up to 12 months when stored according to manufacturers instructions.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.