

## EVERBUILD DEEP GAP FILLER



Colour	Product Code	Pack Size	Box Qty
GREY	RMDEEP1	1Ltr	6

### Product Description

DEEP GAP FILLER is a revolutionary new filler, formulated using ceramic spheres that fill most holes and cracks; especially deep holes, in just one quick application with no need for secondary filling to level off. DEEP GAP FILLER will not shrink, sag or crack and dries to a light grey finish. DEEP GAP FILLER finishes smooth, requiring little or no sanding and can be ready to paint or wallpaper in just 30 minutes. It can be used for repairs to wood, plaster, masonry, cement, stone, brick and rendering.

### Benefits

- Fills in one go- No need to build up layers of filler - fills up to 50mm deep in one application.
- Easy to use - lightweight paste is incredibly easy to apply.
- No sanding required - finishes to a smooth surface.
- No sagging - the lightweight properties of DEEP GAP FILLER prevent sagging even on ceilings.
- Non-shrink - will not shrink back whilst drying.
- Quick drying - ready to paint/paper in just 30 minutes (subject to ambient temperature/conditions)
- Overpaintable with most solvent based and emulsion paints.
- Overstainable
- Internal use.

### Areas For Use

Fills gaps and holes in:

- Plaster
- Brick
- Stone
- Wood
- Render
- Cement
- Masonry

### Limitations

- Do not use in areas subject to constant water immersion.
- Do not use externally.
- Do not use for structural repairs or to nail/screw into.
- Absorption of the filler may be different to the surrounding area. If filler shows through after painting, simply apply further coats.

### Surface Preparation

All surfaces must be clean, dry, free from dust, grease and other contamination.

### Application

Stir DEEP GAP FILLER to a smooth paste. If product is too dry, add a few drops of water and re-stir. Apply using a flexible filler knife, smoothing down to achieve a perfect surface that won't need sanding.

When filling a large surface area, it may not always be possible to achieve a completely level finish. However, DEEP GAP FILLER is very easy to sand if necessary.

Deep holes up to 50mm can be filled in one application with no need to build up in several layers.

Any nail or screw heads should be painted over before filling, to prevent rusting.

### Specific Data

Appearance	Lightweight light grey paste
SG @ 20°C	1.15-1.25g/cm <sup>3</sup> (approx)
Movement Accom	Low/Moderate
Maximum Fill	50mm in one coat – further layers may be built up
Maximum Width	50mm
Application Temp	5°C to 30°C
Drying Time	30 minutes at 20°C 50% R.H.
pH	8.3 – 9.9
Viscosity	50,000-100,000cps. @ 20°C 50% R.H

### Health & Safety

Consult MSDS for full list of hazards.

### Storage

Store at moderate temperatures.

### Shelf Life

24 months from date of manufacture when stored according to manufacturers instructions.

*The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.*