

## Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

---

# Soudal Soudaflex 40FC

---

Revision: 8/04/2014

Page 1 from 3

Reference nr DOP: 230082

Unique identification code of the product type:

**Soudal Soudaflex 40FC**

Intended use or uses of the construction product:

**Sealant for facade for interior and exterior application.**

**Sealant used for pedestrian walkways for interior application.**

Construction product in accordance with applicable harmonised specifications:

**EN 15651-1:2012: Type F - EXT-INT**

**EN 15651-4:2012: Type PW-INT**

System or systems of assessment and verification of consistency of performance of the construction product, as set out in Annex V:

**System 3**

**System 3: for reaction to fire**

Name and contact address of the manufacturer as required pursuant to Article 11(5):

**Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium**

The notified body:

**GINGER CEBTP, NB 0074 has carried out Determination of Product Type under system 3.**

## Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

---

# Soudal Soudaflex 40FC

---

**Declared Performance**

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class E	EN 15651-1: 2012 EN 15651-4: 2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 15%	
Tensile properties at maintained extension	NF	
Adhesion/cohesion at maintained extension after water immersion	NF	
Tear resistance	NF	
Elongation at break	≥ 25%	
Durability	Pass	

**Conditioning:**

Method A

**Substrate:**

Aluminium

Mortar

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for on behalf of the manufacturer by



Ing. W. Dierckx

Technical Product Manager  
BE-2300 Turnhout, 8/04/2014**CE marking**

In accordance with the CPR Regulation (EU) N° 305/2011



NB 0074

**Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium**

14

Reference nr DOP: 230082

EN 15651-1: 2012

EN 15651-4: 2012

Sealant for facade for interior and exterior application.  
Sealant used for pedestrian walkways for interior application.

**Soudal Soudaflex 40FC**

EN 15651-1:2012: Type F - EXT-INT

EN 15651-4:2012: Type PW-INT

**Conditioning:**

Method A

**Substrate:**

Aluminium

Mortar

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class E	EN 15651-1: 2012 EN 15651-4: 2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 15%	
Tensile properties at maintained extension	NF	
Adhesion/cohesion at maintained extension after water immersion	NF	
Tear resistance	NF	
Elongation at break	≥ 25%	
Durability	Pass	