

EVERBUILD 406 STABILISING SOLUTION



Colour	Product Code	Pack Size	Box Qty
-	STAB5	5Ltr	4

Product Description

EVERBUILD STABILISING SOLUTION is a specially formulated microscopically fine polymer emulsion which penetrates deeply into dusty/chalky and badly weathered surfaces to leave a stable sound base for subsequent decoration with paint/wallpaper/tiling etc. Suitable for both interior and exterior use over plaster, rendering, pebbledash,, stucco, existing painted surfaces, brickwork, blockwork etc.

Benefits

- Stabilises and binds interior and exterior friable surfaces prior to overcoating.

Areas For Use

As an effective stabiliser for Brick, Stone, Render, Concrete, Plaster, Pebbledashing/stucco etc prior to applying a further surface coating.

Limitations

- Ready to use product. Do not dilute.
- Dispose of this product and packaging correctly. Do not allow to enter watercourses.
- Will not restore badly disintegrated render/plaster etc. This will require removing and subsequent re-application.
- It is the user's responsibility to determine suitability for use. If in doubt, please contact Technical Services Department for further advice.
- Do not apply below 5°C.
- Do not apply externally if rain is imminent (within 6 hours)

Surface Preparation

All surfaces must be clean, dry (to touch) and free grease and other contaminants. Remove all loose and flaking material with a scraper and a stiff brush back to a sound surface. Cure all root causes of penetrating damp and remove all moss/mould contamination with EVERBUILD MOSS AND MOULD REMOVER according to the instructions on the container.

Application

This is a ready to use product. DO NOT DILUTE. Apply by brush in one liberal coat. For extremely porous surfaces, apply a second coat when dry. Drying time 2-4 hours depending on temperature, humidity etc.

COVERAGE; 5-10m² per litre depending on porosity of surface and method of application.

STORAGE: Store in cool dry conditions away from direct sunlight between 5 and 30°C . PROTECT FROM FROST.

Specific Data

Colour	Milky white – dries clear
Solids (w/w)	15 – 17%
Viscosity (B4 Flow Cup)	12 seconds
Specific Gravity	1.02 g/cm ³
pH	8 – 9.5
M.F.F.T	0°C
Particle Size	0.1 micron
Drying Time	Touch dry; 2 – 4 hours @ 20°C depending on substrate

Health & Safety

Consult MSDS for full list of hazards.

Storage

Store in cool, dry conditions, between 5 and 25°C. PROTECT FROM FROST

Shelf Life

12 months

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.