

EVERBUILD 408 SUPERSEAL



Colour	Product Code	Pack Size	Box Qty
Clear	WALLSEAL5	5Ltr	4

Product Description

EVERBUILD SUPERSEAL is a high performance solvent based transparent water repellent specially formulated to provide a water repellent finish and prevent attack by water penetration on porous substrates such as brick, stone, masonry, plaster, plasterboard, pebbledash, rendering, porous tiling, grouting etc.

EVERBUILD SUPERSEAL penetrates deep into the treated area and actually chemically bonds to the surface, providing effective water repellency for many years. It is unaffected by ultra violet light and offers improved water beading when compared to other traditional solvent based products. SUPERSEAL can be applied by spray, brush, mop or roller.

Tested in accordance with BS EN ISO 10545-14:1997

Benefits

- Improved durability and beading effect.
- Solvent based, quick drying formula.
- Works on most common mineral surfaces.
- Deep penetrating formula.

Areas For Use

As an effective water repellent on:

- Brick
- Stone
- Render
- Masonry
- Pebbledashing.

Limitations

- Do not apply to damp/wet surfaces.
- Do not apply when raining or when rain is imminent.
- Do not use on non porous surfaces.
- Do not use on wood, plastic or rubber.
- Do not use in fishponds.
- Protect windows and surrounding areas from overspray. Remove any overspray immediately whilst the product is still wet, with a cloth .

NOTE: THE SURFACE TO BE TREATED MAY DARKEN AFTER THE FIRST APPLICATION. ALWAYS TEST A SMALL AREA FIRST PRIOR TO COATING THE WHOLE SURFACE.

Surface Preparation

All surfaces must be clean and sound, free from dirt, mould, algae, grease and other contamination. Carry out surface repairs and fill cracks before application.

Application

Shake can well before use. Apply by low pressure spray, brush or roller.

NOTE: THIS PRODUCT WILL DRY CLEAR.

On vertical surfaces, saturate the wall working from the bottom up, ensuring the entire surface is covered. On horizontal surfaces, flood the entire area then after 10 minutes, spread out with a soft brush, roller or mop to ensure the entire area is covered.

Two coats are normally required; the second coat being applied within 1 hour – as soon as the first coat has soaked in and whilst the surface is still wet. Clean brushes, rollers and spray equipment with white spirits IMMEDIATELY after use.

COVERAGE – Coverage will vary depending on the porosity of the substrate. As a quick guide, brick coverage will be approx. 5 sq. metres per litre for the first coat, 8 sq. metres per litre for the second coat.

DRYING TIME – Approx. 1-2 hours; depending on air temperature.

Specific Data

Colour	Clear liquid.
Active Components	Siloxane resin/solvent blend.
Coverage	5 – 8 m ² / litre depending on porosity and nature of surfaces being treated.
Specific Gravity	0.88 - 0.92
Application Temperature	+5 - 40°C, do not apply where surface temp. exceeds 40°C

Health & Safety

Consult MSDS for full list of hazards.

Storage

Store in cool, dry conditions.

Shelf Life

12 months from date of manufacture.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.