

EVERBUILD QUICK DRYING VARNISH



Colour	Product Code	Pack Size	Box Qty
Gloss	WVARCLG02	250ml	6
	WVARCLG07	750ml	6
Satin	WVARCLS02	250ml	6
	WVARCLS07	750ml	6

Product Description

Everbuild Quick Drying Clear Varnish is a professional, low solvent clear varnish that enhances the natural qualities of wood, and provides long lasting protection.

Everbuild Quick Drying Clear Varnish has been developed specifically to give an ultra-hard, scratch resistant and heatproof, non-yellowing finish.

It is ideal for use on interior wood such as tables, chairs, doors, skirtings, furniture etc.

Benefits

- Low Solvent Formula
- Touch dry in 30 minutes, overcoat after 1 hour.
- Long lasting protection.
- Clear finish, no discoloration.

Surface Preparation

Ensure wood is clean, dry and free from dirt or dust by wiping with a lint free cloth dampened with white spirit, allow to dry before applying varnish.

On varnished wood, remove any unsound varnish and sand the surface with medium grade sandpaper well to a uniformed appearance and then clean with white spirit. Allow to dry thoroughly before applying Everbuild Clear Varnish. On bare wood, sand the surface with fine sandpaper. Always remove excess dust with a cloth before applying varnish.

Application

Stir product well before use and intermittently during application.

Brush apply Everbuild Clear Varnish, following the direction of the wood grain, approximately 2-3 coats will be required for full coverage. It is touch dry in 30 minutes, allow 1 hour in between coats lightly sand the surface before applying the final coat. Always apply the varnish to a wet edge, working systematically across the surface keeping the wet edge moving together as much as possible.

Clean brushes thoroughly with water after use, a little washing up liquid will assist brush cleaning.

If water is accidentally spilt on the surface within 2-3 days of application, remove by wiping gently (do not rub) with a soft cloth.

Note: on application, the varnish will appear slightly white; this quickly turns completely clear as the drying process starts.

Limitations

- Do not use on wood floors or decking.
- Do not use externally.
- Protect from frost and do not use in temps below 10°C.
- To avoid risk of spillage, always transport this tin in a secure and upright position.
- As the manufacturer cannot know all the uses its products may be put to, it is the user's responsibility to determine suitability for use. If in doubt, contact Technical Services Department for advice or refer to technical data sheet.

Coverage Guide

Up to 16 square metres per litre. Coverage will vary depending on the absorbency of the wood.

Health & Safety

See MSDS for full list of hazards.

Storage

Store in cool dry conditions between + 5 and +25°C. Storage outside these conditions will dramatically reduce shelf life. PROTECT FROM FROST.

Shelf Life

2 years from date of manufacture when stored as directed.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.